

SKY-1500IP Network IP Security Camera



Dual Codec - MPEG4/MJPEG Selectable
High Resolution 520 Lines / D1
Day/Night with Mechanical IP Cut Filter
Power-Over-Ethernet Ready
Real-Time Sync'd A/V Stream
Advanced Motion Detection
Adjustable Bandwidth and Resolution

Technical Specifications

Image Sensor	Sony Super HAD 1/3" CCD HQ1 Digital Signal Processor
Day/Night	Mechanical IR Cut Filter
Compression	M-JPEG / MPEG-4 Selectable
Camera Resolution	520 TV Lines
Video Adjustments	Max AGC, Contrast, Brightness, BLC, Saturation, Sharpness, Flickerless
Exposure	AGC / AWB
Electronic Shutter	1/60 - 1/100,000 sec
Sensitivity	Color: .5 lux @ F1.2 B & W: .03 lux @ F1.2 IR 400 ~ 700nm
Auto-Iris Type	DC-Iris
MPEG-4 Resolution	Full D1, Half D1, CIF
MPEG-4 Frame Rate	30, 24, 15 fps
MPEG-4 Bitrate	Multi-Level, 64Kbps - 8Mbps
Motion Detection	Advanced Multi-Zone
Privacy Masking	3 Zones
Time Stamp	Time/Date/Title
Digital Signature	M-JPEG Watermark

Password Authorization	Multi-level / Multi-users
Video Output	1.0 VpP, 75 ohm, composite
Audio	16bit, 8 kHz sample rate
Synchronization	in MPEG-4 Mode
Microphone	Built-in, Omnidirectional
SD Interface	Alarm and Scheduled Recording
Alarm	I/O 1 input/1 output
USB Interface	Configuration/Upgrade
Serial Port	9 pin RS232/RS485
Power Requirement	12V DC / POE
Weight	.73 lbs. (332 grams)
Dimensions	2.36" (W) x 1.77" (H) x 3.70" (D) 60 (W) x 45 (H) x 94 (D) mm
Operating Temperature	0 C ~ 50 C (32 F ~ 122 F)
Approvals	FCC, CE, RoHS
Network Interface	Ethernet 10/100 Base-TX, MDIX
Network Protocol	TCP/IP, DHCP, HTTP, UDP, FTP, SNMP, ICMP, DDNS, DNS, UPnP, PPPoE, ARP
Accessories Provided	AC Power Adapter, Surveillance Software